


4101 Garland Dr., Fort Worth, TX 76117
Phone 817.485.6073 Fax 817.428.6008
www.starindustries.com

Forklift

BUCKETS

Operator's Manual

Quick-tach



Slip-on-fork



BEFORE USE, READ AND UNDERSTAND THE COMPLETE OPERATOR'S MANUAL.

EXPAND ... THE USE OF YOUR FORKLIFT

- ▶ Load Sand & Gravel
- ▶ Remove Snow
- ▶ Handle Roof Tear-Off Trash
- ▶ Backfill Behind High Walls
- ▶ Do Job Site Clean-Up
- ▶ Elevate Roof Gravel

Reaches where loaders can't...

Designed for extendable-reach forklifts. Star Forklift Buckets permit placement of material far beyond the reach of a loader.

Stop paying extra for a loader...

The cost of a Star bucket is less than a two month loader rental.

Built to last...

Rugged heavy-duty construction ensures long life.

DANGER - DO NOT USE WITHOUT INSTALLING RETAINING PINS behind the heel of each fork and securing with hair pins or cotter pins

Safety chain(s) must also be used. Wrap chain around a strong part of the fork carriage and secure with locking grab hook.

Operator's Manual also available online.

BEFORE USE, READ AND UNDERSTAND THE COMPLETE OPERATOR'S MANUAL.

If you need clarification or any additional information call your Star dealer or call Star Industries @ 1-800-541-1797 during normal business hours.

Customers Who Bought this product also bought



Safety Work Platforms -
Turn your forklift into an aerial work platform



Lift Hooks -
Lift up to 22,000 lbs safely and securely



Concrete Hoppers -
Turns your forklift into a concrete placer.

Visit www.Starindustries.com or call us at 800-541-1797 for more information on these and other great products.

Star Industries forklift buckets for telehandlers are built in two styles, Slip-on-the-Forks style and Quick-Tach Style. They are available in various widths and capacities to match required applications. Both styles are designed for all makes and models of telehandlers including but not limited to Cat, Carelift, Gehl, Genie, Gradall, Ingersoll Rand, JCB, JLG, Lull, Manitou, Mustang, Pettibone, Skytak, and Xtreme. The bucket size/volume should be matched to the heaviest material being handled, the lift capacities of the telehandler, and the boom positions in which the bucket will be used to ensure the telehandler rated capacity will not be exceeded.

In view of the fact that the load center of neither style of bucket exceeds the standard 24" load center of the telehandler a separate load chart is not necessarily required. However when capacities are being calculated the weight of the bucket must be included with weight of the material carried. In the case of the quick-tach bucket the weight of the carriage and forks (which are removed to install the bucket) in some cases offsets the weight of the bucket and then only the weight of the load has to be considered.

Star forklift buckets are designed to handle loose materials and are not intended for excavation or digging which in some cases could damage the boom of some telehandlers. Good applications include but are not limited to, loading gravel, sand, or dirt out of a pile, jobsite clean-up, snow removal, backfill behind high walls, elevating roof gravel, spreading sand and gravel, and handling various landscape materials.

WARRANTY PROCEDURE:

Upon notification, Star Industries will determine if the product will need to be returned to Star Industries. Where An inspection or repair will take place. Or the Star Dealer, or other entity, can be authorized to make the inspection/repair at their location, or if circumstances dictate other solutions. Dealer or other entity repairs **must have prior written authorization**. Reimbursement will be at the current "Star Warranty Labor Rate" and will not include reimbursement for offsite travel. A Warranty Claim Form must be submitted within 45 days of warranty repair authorization to receive credit for repair.

A return authorization number must be obtained from Star Industries before a product can be returned for inspection and/or warranty and that number must appear on the return shipping label. Upon inspection, Star Industries will determine if the product is defective and if so, whether it will be repaired or replaced. Repair or replacement is at the discretion of Star Industries. Transportation charges to Star Industries are not covered under the warranty and must be prepaid by dealer or customer unless it is within the first two years of warranty. In which case, if evidence acceptable to Star Industries, is provided that the product is defective and the return is from within the continental United States or Canada, Star will arrange for return shipment at Star Industries expense. Products found to be defective within the initial two year period and returned to Star Industries for repair or replacement will be returned to the dealer or customer freight prepaid providing it is within the continental United States or Canada. Warranted products to be shipped outside the United States or Canada and those warranted after the initial 2 years will be shipped freight collect. Unwarrantable products will be returned freight collect at the request of the dealer or customer, otherwise they will be destroyed.

LIMITATION OF DAMAGES:

Star's obligation under this warranty shall not include costs of installation, duty, taxes or any other charges whatsoever or any liability for direct, indirect, incidental or consequential damages or delay. Star's liability for any and all losses and damage to purchaser resulting from any cause whatsoever, including negligence or breach of form of warranty, express or implied by Star, alleged damage for defective goods, irrespective of whether such defects are discoverable or latent, shall in no event exceed the purchase price of the particular goods. Products repaired or replaced under this warranty are warranted only for the remainder of the original warranty. Any improper use including operation after discovery of defective or worn parts not approved by Star or any alteration or repair by others in such manner as in Star's judgment affects the product materially and adversely shall void this warranty.

THE FOREGOING WARRANTIES ARE EXCLUSIVE AND ARE IN LIEU OF ALL OTHER WARRANTIES (WHETHER WRITTEN, ORAL OR IMPLIED) INCLUDING WARRANTIES OF MERCHANTABILITY AND WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE.

Star Industries Limited Warranty

Star Products are warranted to the original purchaser against defective workmanship and/or materials (when properly installed, used, and maintained) for a period as specified below from date of delivery to the customer by an authorized Star Dealer or direct from Star Industries. This warranty does not cover misuse, abuse, normal wear and tear, or accidental damage.

- 5 year Warranty:** All Star products except as noted below. (Includes HD Auger Drives & most non-hydraulic products)
- 2 year Warranty:** Medium Duty Auger Drives
- 1 year Warranty:** Auger Bits and Auger Accessories (excludes auger drives), Crane Forks, Grapples, Angle Broom, Self Dumping Hoppers, Replacement Forks, and Over the Bucket Forks
- 6 month Warranty:** Concrete Mixers




WARRANTY CLAIM NOTIFICATION:

Product defects should be reported to the Star dealer from whom the product was purchased or to Star Industries in writing promptly after discovery. Preferably photographs showing the defect should also be provided along with a written report of circumstances involved. Warranty claims not made within 30 days after discovery of the defect shall be null and void.

WARRANTY DETERMINATION:

If a warranty claim is found worthy and made within the warranty period we reserve the right at our discretion to repair existing defects or to replace it with the same or current model free of charge or to issue a credit for the reasonable cost of repair or take possession of the equipment and issue reimbursement for the calculated value.

DANGER - DO NOT USE WITHOUT INSTALLING RETAINING PINS behind the heel of each fork and securing with hair pins or cotter pins

EMPTY FORK POCKET	1½" TO 2¾" THICK FORKS	2-½" TO 3" THICK FORKS
		
<p>Note: Stop Pin on some attachments is not removable</p>	<p>Stop Pin must be in lower hole when using 1-½" to 2-¾" thick forks</p>	<p>Stop Pin must be in Upper hole when using 2-½" to 3" thick forks</p>

Safety chain(s) must also be used. Wrap chain around a strong part of the fork carriage and secure with locking grab hook.

