

# SHAFT MOUNTED FORKS AND BARS



These shaft-mounted forks suit all pin-type carriages for telehandlers and rough-terrain forklifts, including models from: JLG, Cat, Skytrack, JCB, Genie/Terex, SkyJack, Pettibone, Xtreme , Gehl, Gradall, and Ingersoll Rand.

- ➔ Designed to precisely fit each individual machine
- ➔ Forged from heat-treated premium carbon-steel
- ➔ Greater strength and resistance to bending
- ➔ Fork life is rated to at least 1 million lift cycles
- ➔ Including general purpose and block forks

## 5 REASONS STAR FORKS ARE BETTER

- 1 **No shortcuts.**  
All forks are forged from a single piece of steel, then fully heat-treated, quenched and tempered for a minimum yield strength of 825 Mpa.
- 2 **Certified production methods.**  
Welding processes are certified in accordance with ISO 3834-2.
- 3 **Rigorous testing.**  
Fork heels and welds are subjected to full MPI crack-testing on all welds and the heel area by certificated operatives.
- 4 **Full part traceability.**  
Each fork is stamped with manufacturer's identification, specified capacity and load centre, week of manufacture and production works order number.
- 5 **Standards-compliance.**  
All forks are guaranteed to meet or exceed the requirements of the national and (such as ISO2328 and ISO2330 and ANSI ITSDF B56.11.4) with regards to mounting details, load-, fatigue- and impact-tests.



4101 Garland Drive Fort Worth TX 76117  
 Phone | 817-485-6073 Fax | 817-428-6008  
**USA & Canada Toll Free 800-541-1797**

**www.starindustries.com**  
 Operating Manual and Safety Information available online.

# PRODUCT OPTIONS



Star Industries Fork Selector  
for ITA and Shaft Mounted Forklifts



## REPLACEMENT FORKS (BARS SOLD SEPARATELY)

Model	Dimensions	Collar	Shaft	Rated Capacity/pair @24"LC	Used with
SF19	2"x2"x48"x20.5"CL	¾" Offset	2.25"	2,050 lbs	Genie Terex 5519 & 6622
SF20	2"x4"x48"x20.5"CL	¾" Offset	2.25"	6,900 lbs	
SF21	2"x4"x60"x20.5"CL	¾" Offset	2.25"	6,900 lbs	
SF24	2"x4"x72"x20.5"CL	¾" Offset	2.25"	8,500 lbs	
SF34	2"x2"x48"x20.5"CL	Inline 4" wide	2"	2,050 lbs	Genie/Terex 6K & 8K, Gradall 6K,9K,&10K w/2" shaft
SF35	2"x5"x48"x20.5"CL	Inline	2"	10,500 lbs	
SF36	2"x5"x60"x20.5"CL	Inline	2"	10,500 lbs	
SF37	2"x5"x72"x20.5"CL	Inline	2"	10,500 lbs	
SF38	2"x5"x96"x20.5"CL	Inline	2"	10,500 lbs	
SF39	2"x2"x48"x20.5"CL	Inline 4" wide	2.25"	2,050 lbs	Genie/Terex 10K, JLG 6K, 9K, 10K, & 12K up to Oct 2009
SF40	2.25"x4"x48"x20.5"CL	Inline	2.25"	12,600 lbs	
SF41	2"x6"x60"x20.5"CL	Inline	2.25"	12,600 lbs	
SF42	2"x6"x72"x20.5"CL	Inline	2.25"	12,600 lbs	
SF43	2"x6"x96"x20.5"CL	Inline	2.25"	12,600 lbs	
SF110	2.36"x6"x48"x22.75"CL	Inline	2¾"	18,200 lbs	Genie GTH 1244 & 1544
SF111	2.36"x6"x60"x22.75"CL	Inline	2¾"	18,200 lbs	
SF112	2.36"x6"x72"x22.75"CL	Inline	2¾"	18,200 lbs	
SF113	2.36"x6"x96"x22.75"CL	Inline	2¾"	18,200 lbs	
SF44	2"x2"x48"x22.75"CL	1¼" Offset	2¼"	2,050 lbs	JCB 506, 507, & 508, 550 & 512-53, 940
SF45	2.25"x4"x48"x22.75"CL	1¼" Offset	2¼"	12,160 lbs	
SF46	2"x6"x60"x22.75"CL	1¼" Offset	2¼"	12,600 lbs	
SF47	2"x6"x72"x22.75"CL	1¼" Offset	2¼"	12,600 lbs	
SF48	2"x6"x96"x22.75"CL	1¼" Offset	2¼"	12,600 lbs	
SF49	2"x2"x48"x24.25"CL	¼" Offset 4" Wide	2"	2,050 lbs	All Skytraks & Lulls w/2" Shafts Xtreme XR842, XR1045, XR1245, XR1255, XR1270
SF50	2.25"x4"x48"x24.25"CL	¼" Offset	2"	12,160 lbs	
SF51	2"x6"x60"x24.25"CL	¼" Offset	2"	12,600 lbs	
SF52	2"x6"x72"x24.25"CL	¼" Offset	2"	12,600 lbs	
SF53	2"x6"x96"x24.25"CL	¼" Offset	2"	12,600 lbs	



4101 Garland Drive Fort Worth TX 76117  
Phone | 817-485-6073 Fax | 817-428-6008  
USA & Canada Toll Free 800-541-1797

[www.starindustries.com](http://www.starindustries.com)  
Operating Manual and Safety  
Information available online.

Model	Dimensions	Collar	Shaft	Rated Capacity/pair @24"LC	Used with
SF59	2"x2"x48"x24.25"CL	¼" Offset 4" Wide	2.25"	2,050 lbs	All Skytraks, Lulls, JLG Cat (built by JLG) TL642, TL943, TL1055, TL1255, JLG G5-18 w/2.25" Shafts
SF60	2.25"x4"x48"x24.25"CL	¼" Offset	2.25"	12,160 lbs	
SF61	2"x6"x60"x24.25"CL	¼" Offset	2.25"	12,600 lbs	
SF62	2"x6"x72"x24.25"CL	¼" Offset	2.25"	12,600 lbs	
SF63	2"x6"x96"x24.25"CL	¼" Offset	2.25"	12,600 lbs	
SF64	2"x2"x48"x28"CL	Inline	2"	2,050 lbs	Ingersoll Rand VR series 6 to 10K Skyjack same
SF65	2"x5"x48"x28"CL	Inline	2"	10,500 lbs	
SF66	2"x5"x60"x28"CL	Inline	2"	10,500 lbs	
SF67	2"x5"x72"x28"CL	Inline	2"	10,500 lbs	
SF68	2"x5"x96"x28"CL	Inline	2"	10,500 lbs	
SF69	2"x2"x48"x22"CL	¾"X 4" wide	2⅜" (60mm)	2,050 lbs	CAT TH360, TH460, TH560, Th580, W/2⅜" SHAFT Can be used with JLG G6-23A (only difference is G6-23A offset is 0.285)
SF70	2"x5"x48"x22"CL	¾"X 4" wide	2⅜" (60mm)	10,500 lbs	
SF71	2"x5"x60"x22"CL	¾"X 4" wide	2⅜" (60mm)	10,500 lbs	
SF72	2"x5"x72"x22"CL	¾"X 4" wide	2⅜" (60mm)	10,500 lbs	
SF73	2"x5"x96"x22"CL	¾"X 4" wide	2⅜" (60mm)	10,500 lbs	
SF74	2"x2"x48"x24.25"CL	1" Offset	2"	2,050 lbs	Gehl RS & DL Series 6K, 9K, 10K, & 12K with 2" Shaft
SF75	2.25"x4"x48"x24.25"CL	1" Offset	2"	12,160 lbs	
SF76	2"x6"x60"x24.25"CL	1" Offset	2"	12,600 lbs	
SF77	2"x6"x72"x24.25"CL	1" Offset	2"	12,600 lbs	
SF78	2"x6"x96"x24.25"CL	1" Offset	2"	12,600 lbs	
SF80	2.25"x4"x48"x24.25"CL	1" Offset	2.5"	12,160 lbs	Gehl DL 11, DL12 & RS12 with 2.5" dia shaft which are available with approx. 3 week lead time
SF81	2"x6"x60"x24.25"CL	1" Offset	2.5"	12,600 lbs	
SF82	2"x6"x72"x24.25"CL	1" Offset	2.5"	12,600 lbs	
SF83	2"x6"x96"x24.25"CL	1" Offset	2.5"	12,600 lbs	

## REPLACEMENT BARS (FORKS SOLD SEPARATELY)

Exact measurements needed

Model	Finished shaft size (dia.)	Carriage width (out to out)	Overall shaft length (out to out)	Weight
FP20048	2.0"	48"	51.5"	48 lbs
FP20060	2.0"	60"	63.5"	59 lbs
FP20072	2.0"	72"	75.5"	69 lbs
FP22548	2.25"	48"	51.5"	60 lbs
FP22560	2.25"	60"	63.5"	74 lbs
FP22572	2.25"	72"	75.5"	87 lbs



4101 Garland Drive Fort Worth TX 76117  
 Phone | 817-485-6073 Fax | 817-428-6008  
**USA & Canada Toll Free 800-541-1797**

**www.starindustries.com**  
 Operating Manual and Safety Information available online.